

SaturnFans.com Forums > Categories > How-To Library

Removing Seats From a S-Series Model


Welcome, Zeebins.
You last visited: 01-22-2020 at 06:58 PM
[Private Messages](#): Unread 0, Total 20.

User CP FAQ Members List Groups Calendar Chat Room New Posts Search Quick Links Log Out

Google Custom Search

Search SaturnFans.com

[Advanced Forum Search](#) | [Advanced Photo Search](#)



02-18-2005, 07:58 PM

#1

94sc2boy

Member

Join Date: Sep 2000
Location: Morro Bay, CA
Posts: 482

[94sc2boy's Photos](#)

1994 SC2

Removing Seats From a S-Series Model

This is how to remove the seats out of my 94 sc2. I believe it is relevant to 95 and prior, but don't quote on that.

THIS is great because you can add new seats, or remove them for racing. I removed my passenger seat when I moved and was able to move my 27 inch tv with all my other worldly possessions.

First you need a torx e10 bit. This is a female torx much like a regular socket, but 6 stared.

There are two bolts up front and two in the back.

I've had some trouble with the back ones, because they are so close to the seat frame rails. For this I recommend getting a torx SOCKET THAT IS THIN. 3/8 drive will work the best. And the thinner the diameter of the socket the easier to get it next to the frame.

I've also had luck with vice grips on ones that are too close to the frame. Once the 'stars' ends are off you can use just a regular wrench. Hell if You don't want to buy the sockets you can just grind them down and use a regular socket or wrench.

Mine had a switch that connected to the seatbelt sensor. I plugged it back in just in case it would beep forever.

My drivers side seat has 200k miles and 11 years on it. The lumbar adjust had been broken for sometime. So I wanted to put in a brace to keep the foam firm against my back.

At the bottom of the seats teh material meets in a plastic 's' clip. It runs the width of the seats. I used a screw driver and pryed one side out of the other. The bottom seat is much easier because the plastic clips over the seat frame.

Once you have the material free you just take off the lumbar support with a horseshoe ring remover just like your door handle.

Then I pulled the material up. I pulled it over its self to keep the rest of it tight. Instead of pulling the whole thing off like a tshirt. There are two pieces of velcro running along the inside of the seat back to keep it on there.

I saw that the foam was split and just put a piece of 1x4 in there. I then whacked the frame to 'pinch' it in there. Take a look

Good luck

REWARD EXCELLENCE!

Rate the quality of this post and help 94sc2boy reputation points. Click the reputation button near the bottom left corner of this message box. Thank you!

SaturnFans.com Sponsored Links

« [Previous Thread](#) | [Next Thread](#) »

Currently Active Users Viewing This Thread: 1 (1 members and 0 guests)

[Zeebins](#)

Posting Rules

Forum Jump

How-To Library

Go

www.saturnfans.com/forums/showthread.php?t=49473

1/2

Posting Rules

You **may not** post new threads

You **may** post replies

You **may** post attachments

You **may** edit your posts

BB code is **On**

Smilies are **On**

[IMG] code is **On**

HTML code is **Off**

[Forum Rules](#)

Similar Threads				
Thread	Thread Starter	Forum	Replies	Last Post
Removing seats with E10 bolts...	Chaka	S-Series General	17	04-14-2014 04:00 PM
Removing The Rear Seats?	srl1104	S-Series Tech	10	04-01-2007 06:19 PM
Removing and Washing Cloth Seats!	LoweredVue	Vue General	1	07-05-2005 08:49 PM
SL model Seats	Motley00	S-Series General	14	01-19-2004 11:45 PM
Need help removing seats	Son93SL2	Miscellaneous Tech	11	04-21-2001 10:26 AM

All times are GMT -5. The time now is 12:35 AM.

Search SaturnFans.com

[Advanced Forum Search](#) | [Advanced Photo Search](#)